## CO<sub>2</sub> PORTABLE FIRE EXTINGUISHERS



## PRODUCT DESCRIPTION

NAFFCO  $CO_2$  gas extinguishers are characterized by their high performance for fires including items at risk for electrical shorts like computer, office equipment and generators etc.  $CO_2$  is non conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings. Suitable for Class B fire risks.



## **FEATURES**

- Carbon Dioxide is the trusted non-conductive cleaning agent and is most effective for dealing with electronic equipment fires. CO<sub>2</sub> is suitable for use on Class B and Class C fires.
- TYPICAL USES: For protecting sensitive electronic equipment in offices, classrooms, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses
- such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.
- Not suitable for use on fires involving cooking oil and grease. Recommended for use on sensitive electronic equipment.

## **SPECIFICATION**

31 2011 10/411014								
Model Number	N 05L C	NC 5L	N 10L C	NC 10L	N 15L C	NC 15L	N 20L C	NC 20L
Agent Capacity	5 lb. (2.27 kg)		10 lb. (4.54 kg)		15 lb. (6.8 kg)		20 lb. (9.07 kg)	
UL Rating	5-B:C		10-B:C		10-B:C		10-B:C	
Discharge Time	9 sec.		9 sec.		15 sec.		20 sec.	
Range (FT/M)	4-8/1.2-2.4		4-8/1.2-2.4		4-8/1.2-2.4		4-8/1.2-2.4	
Bracket	Wall		Wall		Wall		Wall	
Ship Weight	13.75 lb. (6.3 kg)	13.36 lb. (6.7 kg)	27.75 lb. (12.6 kg)	26.72 lb. (12.14 kg)	37.75 lb. (17.1 kg)	35.64 lb. (16.2 kg)	49 lb. (22.2 kg)	47 lb. (22.2 kg)
Unit Height	17.375 in. (44.1 cm)	17.2 in. (43.7 cm)	19.75 in. (50.2 cm)	19.75 in. (50.2 cm)	26.375 in. (67 cm)	26.375 in. (67 cm)	26.875 in. (68.2 cm)	26.875 in. (68.2 cm)
Unit Width	8.25 in. (21 cm)	8.267 in. (21 cm)	12 in. (30.5 cm)	12 in. (30.5 cm)	12 in. (30.5 cm)	11.417 in. (29 cm)	13 in. (33 cm)	12.598 in. (32 cm)
Unit Diameter	5.25 in. (13.3 cm)	5.25 in. (13.3 cm)	6.89 in. (17.5 cm)	6.89 in. (17.5 cm)	6.89 in. (17.5 cm)	6.89 in. (17.5 cm)	8 in. (20.3 cm)	8 in. (20.3 cm)
Cylinder Material	Aluminum							